

675TC Series

Medical Vacuum Sealer



Temperature Controlled Vacuum Sealer with Gas Purge

Perfect for packaging Moisture and Oxygen Sensitive products in critical packaging Environments. Total process control for Medical & Pharmaceutical Packaging

PERFORMANCE

The New 675TC delivers equivalence throughout your facility with repeatable, reliable performance. The 675TC Vacuum Sealer is designed for packaging moisture and oxygen sensitive products. Built in features offer flexibility, protection and performance.

To further enhance production the machine is available with a Dual Heat option. The vacuum sealer is easily mounted on an ergonomic machine stand or can be placed on a tabletop.

PROCESS VALIDATION

Fully lock out protected, alarmed, digital process control. The user friendly LCD touch screen and high speed PLC provide the confidence that all process parameters are maintained Seal-to-Seal. External Verification Ports offer ease of Calibration.

CUSTOMER SERVICE

Our Sales and Technical Support teams are ready to assist you when you call. "Talk to a real person", not voice-mail, about your application, establishing seal parameters, custom projects or parts and service. "We're Listening"

TECHNOLOGY & INNOVATION BUILT-IN

Password protected digital control of all Seal parameters, Five Operating Modes, Six Seal Process Recipes, Visual & Audible Alarms and Calibration Screens. Stainless Steel cases withstand harsh environments and resist the effects of biocides.

SAFETY

Standard Safety features include Safe Low Pressure Jaw Close, Emergency Stop Button, Internal 'Coyote' high temperature limit, and thermal overload protection.



MEDICAL VACUUM SEALER

BUILT-IN FEATURES

Full Digital, High-Speed, PLC Controller with Color enhanced LCD Touch screen HMI.

Password protected digital control of:

All Seal parameters; temperature, time, pressure

6 Seal Process Recipes

Alarm Settings

Calibration Screens

5 Selectable Operating modes:

Gas-Vac-Seal (1-99 cycles)

Vac-Seal

Seal Only

Vac-Gas-Vac-Seal

Vac-Gas-Seal (1-99 Cycles)

Visible and Audible Alarms:

Cold Seal Temperature Profile

Jaw Obstruction

Seal Temperature with Settable High & Low Alarms

Seal Pressure with Settable High and Low Alarms

Stainless Steel Enclosure

Gas Purge Standard

Retracting Vacuum Nozzles (2)

Standard 3/8" wide Upper Heating elements

Electronic Footswitch Activator

External Verification Ports for Calibration of:

Seal Temperature

Seal Time

Seal Pressure

Vacuum Pressure

SAFETY FEATURES

Emergency Stop

Safe Low Pressure Jaw Close

Internal 'coyote' high temperature limit

Thermal overload protection

CLEANROOM FEATURES

Non-Particle generating Venturi Vacuum System

Isolated Exhaust Port

OPTIONS

Selectable Dual Heat or Upper Heat Only

Product Support Tray

Vacuum Moisture & Particle Filter

220VAC

CE Certification

Initial Calibration

Exhaust Silencer

Multi Position Machine Stand

SPECIFICATIONS

Seal Length: 20", 25", 30"

Seal width: 3/8"

Vacuum Pressure: Up to 26 in Hg Standard

Suction Flow: 2.3 SCFM @ 90PSI

Requirements:

Power: 120V 20A Dedicated Circuit

220V 10A Dedicated Circuit

Compressed Air: 4.6 SCFM @ 90 PSI

Case Size: 20" W x 13" D x 8" H

Seal Bar Length: Seal length + 4"

Approximate Weight: 65 lbs



675 TC Vacuum sealing medical pouches

TWO YEAR WARRANTY

The Accu-Seal 675TC Series Vacuum Sealers are designed, built and tested to give years of reliable, trouble free service. We stand behind our products with a two-year warranty on Parts and Labor. Consumables excluded*

BUILT TO LAST

Accu-Seal validatable medical pouch sealers are manufactured in the USA using the highest quality materials and components for unmatched product quality and trouble free performance. Stainless steel cases are designed for ease of maintenance and cleaning. All cables and tubing enter or exit the case through bulkhead fittings.



Pictured: 30" 675TC on Stand with Tray

[Compare the Features...Experience the Difference](#)



225 Bingham Dr., Suite B
San Marcos, CA 92069
800-452-6040 / 760-591-9800

www.accu-seal.com
email: info@accu-seal.com



北京韩卢科技发展有限公司

Beijing Hanlu Development Co., Ltd.

地址: 北京市西二环菜户营58号财富西环2306室 邮编: 100054
电话: 010-63357760 63356874 传真: 010-63356974
邮箱: hanlu@hanlu.com.cn 网址: <http://www.hanlu.com.cn>